

GASOLINE Generator - 3000rpm

Technical Data

HYUNDAI
POWER PRODUCTS

GENERATOR		HY15000LE	HY15000LE-3
Frequency	Hz	50	50
Rated Power	KW	10.0	12.5
Max. Power	KW	11.0	13.75
Voltage	V	220	220/380
Current	A	45.5	19
Plugs		1x16A / 1x32A	1x16A / 1x32A
Display		LED5/LED3	LED5/LED3
Fuel tank capacity	L	25	25
Fuel consumption @100% load	L/H	6.4	6.4
Sound level @ 7m	dBA	79	79
DC output	V/A	12 / 8.3	12 / 8.3

ENGINE		D740	D740
Engine type		Gasoline	Gasoline
Power	KW	15	15
Start		Electric	Electric
Displacement	CC	744	744
Oil Capacity	L	1.1	1.1

ALTERNATOR		AL15	AL15-3
Power	KVA	12.5	12.5
Power Factor		1	0.8
Voltage Regulation		AVR	AVR

DIMENSIONS & WEIGHT			
Net Weight	Kg	144	144
Gross Weight	Kg		
Machine size	mm	930x555x580	930x555x580



LED5

PRECISE OVER LOAD PROTECTION



LED3

Optional Accessories



ATS control box(50A)



Remote controller: 1+2
ATS sensor: 2



Push wheel kit

Electrical standard and options

1-phase(1x16A European sockets)	●
1-phase(1x32A European sockets)	●
American;UK;Australian sockets	○
Display LED5	●
Display LED3	○
Precise overload protection	●
Common overload protection	○
DC output:12V / 8.3A	●
Earth connection	●
ATS connector	○
Remote control	○
ATS control box(50A)	○

Mechanical standard and options

Frame tube diameter 32mm	●
Basic color black	●
Alternator: 100% copper /Steel plate Q195	●
Alternator: 100% copper /Silicon steel plateDW800	○
Push wheel kit	○

Option : ○ Standard feature : ● No available : ✕

Recommended Spare Parts



Air filter core



Fuel filter element